IL650

Interactive Flat Panel

Highlights

Interactive displays have become one of the most powerful office tools today, replacing traditional meetings and trainings with a new style of business communication that's proven to enhance meeting efficiency, training effectiveness, collaborative discussion, and team building. A winning solution for your business, the BenQ Interactive Flat Panel IL650 combines the power of infrared touch panel and multimedia connectivity to maximize your presentations. Designed with safety and flexibility in mind, the IL650 is easy and simple to install in any office setting using a VESA wall mount.



Infrared 2 Points Touch Technology

Pair the IL650 with Windows® 8 / Windows® 7 and watch the infrared touch technology work its magic turning the displayed image or spreadsheet figure into a multi-touch screen. Trainer or speaker can invite audiences to come up to the board for a quick contest and trial.



Ambient Light Sensor

The IL650 is built with an ambient light sensor to detect the amount of ambient lighting in its surrounding and adjust the display setting accordingly without user intervention. This means the audience can always enjoy optimal picture quality in office.



Integrated Speaker

To help professional elites gain the competitive edge by enriching their meeting with multimedia resources, BenQ has built 12W speakers into the IL650. The use of videos, music and sound effects make every presentation more engaging and effective.



B C 620	0000	9 9	
) No. (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	-	audio in (Audioz) Audio in (Audioi) yuga in	(4) VIDEO IN(YPbP) (5) RS232C IN/OUT (6) DVI-IN (7) HDMI
AC OUT AC IN ACSWITCH ON/OFF	SPEAKERS (R/L) (IL650 not available) AUDIO OUT (R/L)	(I) VGA OUT (I) AV IN (I) AV OUT (I) VIDEO IN(S-VIDEO)	B DISPLAY PORT P RJ-45

Specifications			
Screen Size	65"		
Type	PID		
Light Source	E-LED		
Active Area (inch)	56.2" H x 31.6" V		
Resolution (pixels)	FHD 1920 x 1080 (16:9)		
Brightness (typ.)	360 cd/m ²		
Native Contrast Ratio (typ.)	4,000:1		
Response Time (GTG)	8 ms		
Pixel Pitch (H x W)	0.744 H x 0.744 W mm		
Frame Rate	60Hz		
Viewing Angle (H / V)	178 ⁰ /178 ⁰		
Color Gamut (x% NTSC)			
Color Depth	72%		
•	10-bit (8-bit+FRC), 1.07 billion		
Technology	IR 2-point touch		
Resolution (points area function)	4096 x 4096		
Capacity	2 simultaneous touches		
Accuracy	<1.5mm (central area), <2.5mm (marginal area)		
Touch Output	USB 2.0		
OS Supported	Win 2k / XP / Vista / W7, Linux,		
	Mac 10.4-10.6 32 bit		
USB (Touch to External PC)	0		
Power (AC) Input / Output	0/0		
Power Switch	0		
VGA Input / Output	0/0		
DVI Input / Output	O / X		
HDMI Input / Output	0/X		
Composite Video In / Out (BNC)	0/0		
Component In (YPbPr, RCA)	0		
S-Video In / Out	0 / X		
DisplayPort Input	0		
USB Player (Photo, Video)	X		
RS232 Input / Output	0/0		
OPS Slot	X		
RJ45 Port	0		
Audio W (Amp)	12W + 12W		
Internal Speaker	12W x 2		
Power Supply	AC 100~240V, 50 / 60 Hz		
Power Consumption (Max)	<265W		
Power Consumption (Standby)	<0.5W		
Power Consumption (Off)	<0.5W		
Operation Temp (dC)	0° C ~ 40° C		
Storage Temp (dC)	-20° C ~ 60° C		
Usage (hrs/days)	24/7		
Weight (without / with packing)			
Dimension (W x H x D)	143 lbs / 165 lbs 60" x 35" x 4.2"		
Bezel Width (T / B / L / R)			
	1.45" / 1.45" / 1.73" / 1.73"		
VESA Wall Mounting (mm)	400 x 400 (4 Holes)		
Remote Controller	0		
PWR Cord	0		
VGA Cable	0		
Quick Start Guide	0		
User's manual electronic file	0		
UPC Code / Part #	8400460-2702-5 / 9H.F0GPQ.NA2		
Stand Accessory (Optional)	P/N: 5J.F0G14.001 (optional, on VESA mount)		
Features			

- Image Setting Source / Volume Control Analog Daisy Chain RS232 Control Daisy Chain ID Setting
 Sharpness Enhancement Proof of Image Retention Diming Control (Adaptive Contrast) Picture in Picture (PIP)
 Picture by Picture (PBP) DVI-HDCP (IL650 / IL460 not available) DVI-HDCP De-Interlacing / Comb Filter
 10-bit Color Processing (IL650 not available) Build-in Video Wall Support Scheduling Ambient Light Sensor
- Total Turn-On Time Diagnostic DC voltage (12v / 5v) Internal Tempurature Sensor ČEC Control









IL650 08-01-13-BQus



15375 Barranca Parkway. Suite A-205. Irvine, CA 92618 👴 Tel: (949) 255-9500 📀 www.BenQ.us







